



16CH PoE NVR 8MP/6MP/5MP/4MP/3MP/1080P/720P HD PoE NVR





















Mobile













HD Output HD IPC

DDNS

Network

Features:

- Support 16 CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/DI/CIF IP video input
 - Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
 - Multi-mode recording: manual / timed / motion / sensor / POS / AI recording
- Playback: 16 CH simultaneous playback
- Search: time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
 - Support POS information overlay on live view and playback
- Express and flexible backup via USB, network and so on
 - Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS: preview, playback, backup, PTZ and configuration
- 16 PoE network ports; IPC can be directly connected to NVR; PoE power supply supported

 Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device

Authorization management, log view and device status view

- Multi-user online simultaneously
- 4K output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

Specifications:

Specifications,			
Model			
System	os	Embedded Linux	
Video	Network Input	16CH IPC input	
	Network Input Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF	
	Output	HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024/ 1024 × 768	
		VGA: 1920 × 1080 / 1280 × 1024/ 1024 × 768	
	Screen Display Mode	1/4/6/8/9/13/16	
	Compression	H.265S /H.265+ / H.265 / H.264	
Audio	Network Input	16 CH IPC audio input	
	Local Input	RCA × 1 (for two-way audio)	
	Local Output	RCA × 1	
	Compression	G.711(U/A)	
Record	Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF	
	Frame Rate	NTSC:30fps; PAL:25fps	
Playback	Simultaneous Playback	Max. 16 CH	
	Search	Time slice / time / event / tag / smart search	
	Smart Search	Highlighted color to display the camera record in a certain period of time,	
		different colors refers to different record events	
	Function	Play, pause, FF, FB, digital zoom, etc.	

Decoding Capability	Live View/ Playback	1×8MP@30fps; 6×1080P@30fps
Alarm	Mode	Manual, sensor, motion, exception, smart events
	Input	Supports IPC alarm input
	Output	Supports IPC alarm output
	Triggering	Record, snap, preset, e-mail, etc.
Network	Interface	RJ 45 × 1 (10/100/1000Mbps)
	Protocol	TCP / IP, IPv4, IPv6, UDP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, HTTP, SMTP, HTTPs, 802.1x, RTSP, RTP, RTCP, WebSocket, SNMP, IGMP, ONVIF
	Incoming/ Outgoing Bandwidth	160/160 (Mbps)
		*When the AI function of the IPC is enabled, the actual incoming bandwidth(max.bitrate) is more than the set value in the NVR.
	Client Connection	Max. 64 users access
Face	Face Detection Performance (AI by IPC)	16 CH
	Face Detection Performance (AI by Device)	2 CH
	Face Match Performance	No
	Statistical Graph of Information	Bar graph
	Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period
Video Structure Analysis	Human/Vehicle Classification(AI by IPC)	16 CH
	Human/Vehicle Classification(Al by Device)	2 CH
	Human/Vehicle Attribute Analysis	Yes (AI by IPC)
Other Functions	Fisheye	Supports fisheye dewarping via Web Client and mobile APP
	Plate Recognition (AI by IPC)	Yes
Mobile Device	os	iOS, Andriod
Storage	HDD Interface	SATA3.0 × 2, max 10T

Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	USB	USB 2.0 × 2
	Remote Controller	Optional
PoE	PoE Ports	100M RJ45 × 16
	Standards	IEEE802.3AF/AT
	Output Power	≤ 150W
Others	Power Supply	DC 48V/3.75A
	Consumption	≤ 10W (without HDD)
	Dimensions (mm)	380 × 268× 45 (W × D × H)
	Working Environment	-10 \sim 50 °C, 10% \sim 90% humidity
	Certificate	CE, FCC
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE

Rear Panels:

