



3MP 4CH 12.5" LCD Wireless Enhanced Bullet/Dome NVR COMBO KITS



.....

KITS Details Features:

- ❖ 4 CH Enhanced Signal Wireless LCD NVR COMBO Kit with Human Body Detection
- ❖ 2 pcs* 3MP HD IP Bullet + 2pcs IP Dome Wireless Camera
- ❖ 1pcs* 4ch 12.5" LCD NVR COMBO
- ❖ 1pcs* Network Cable
- ❖ 1pcs* Mouse
- ❖ 1pcs*12V/2A Power Supply (for NVR)
- ❖ 4pcs*12V/1A Power Supply (for Camera)
- ❖ 200M Signal Transmission Distance

Camera Details Feature

- ❖ 2pcs*3MP Bullet Camera, 3.6mm Fixed Lens, 2pcs IR Array LEDs, 20-30M IR Distance
- ❖ 2pcs*3MP Dome Camera, 3.6mm Fixed Lens, 18pcs SMD IR LEDs, 20-30M IR Distance
- ❖ 2Db WIFI antenna and 100mbps water-proof RJ-45 port
- ❖ Auto match the NVR channel and play video
- ❖ Built-in IR leds, Day and Night monitoring

NVR Details Feature

- ❖ 4CH 3MP 12.5" LCD NVR Combo, Support 1SATA upto 6TB, 2pcs* USB Port
- ❖ 2K/1080P HDMI/VGA video output

- ❖ Built-in 5Db WIFI antennas x 2 + 3Db WIFI x1
- ❖ Real Plug and Play, automatic connecting video
- ❖ Easy QR code to download app and remote login
- ❖ Support iPhone and Android app: Eseecloud

Technical Specifications:

12.5" Wireless LCD NVR		
	Model NO.	.
System	Operating System	Embedded Linux OS
Video Input	Network Video	Max. 4CH 3MP Camera
	Network video input broadband	40Mbps
Video Output	HDMI output	1ch, resolution: 1024x768, 1366x768,1440x900,1920x1080p,2K
	VGA output	1ch, resolution: 1024x768, 1366x768, 1440x900,1920x1080p
Recording	Record mode	Manual/Schedule/Motion/Alarm
	Playback	by time/Event
	Backup	USB backup, network download
Hard Disk	Type	1*SATA
	Max. Capacity	6 TB
Network	Network port	1 - RJ45 10M/100M
	Wireless	2 - 5Db WIFI antennas x 2 for cameras + 3Db WIFI x1 for router
Smart Detection	Human Detection	Human Detection, Motion Detection
Network Control		UPnP (play&plug)/SMTP (email service)/PPPoE (dial-up) DHCP (Automatically obtain an IP address), etc...
Others	Power Supply	DC12V/2A
	USB	2 - USB 2.0 for mouse and USB drive
	Power Consumption (W)	≤5W (Without HDD)
	Operate Temperature (°C)	-10°C~+55°C
	Working Humidity (%) RH	10%~90%
	Dimension	257mm (W) ×210mm (V) ×45mm (H)
	Weight (without HDD)	≤1Kg
Wireless Bullet Camera		
Housing	Model No.:	
	Sensor	1/2.7" Progressive Scan Sensor
	Resolution	3MP / 1080P
	Signal System	PAL/NTSC
	Compression standard	H.265, H.264, H265+
	Minimum illumination	Color: 0.01 Lux; 0 Lux with IR on
	Shutter	AUTO 1/25s - 1/25,000s
	Lens	3.6MM
	LED	2pcs IR Array LEDs

	IR Distance	20-30M
	OSD	Date Time & Title
	White Balance	Auto
	Day&Night	Auto / Color / BW
	3D-DNR	Auto
	Mirror/Flip	On / Off
	Audio	optional
	Video Stream	Main stream: 3MP(2306x1296)@15fps Sub stream: 640x360@15fps
	Network	RJ45 / WIFI 802.11b/g/n
	Working Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
	Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
	Power Input	DC12V-1A
	Power consumption	≤6W
	Dimension	205(L)×70(W)×55 (H)mm
	Weight	0.7kg

Wireless Dome Camera

Housing	Model No.:	
	Sensor	1/2.7" Progressive Scan Sensor
	Resolution	3MP / 1080P
	Signal System	PAL/NTSC
	Compression standard	H.265, H.264, H265+
	Minimum illumination	Color: 0.01 Lux; 0 Lux with IR on
	Shutter	AUTO 1/25s - 1/25,000s
	Lens	2.8/3.6MM
	LED	2pcs IR Array LEDs
	IR Distance	20-30M
	OSD	Date Time & Title
	White Balance	Auto
	Day&Night	Auto / Color / BW
	3D-DNR	Auto
	Mirror/Flip	On / Off
	Audio	optional
	Video Stream	Main stream: 3MP(2306x1296)@15fps Sub stream: 640x360@15fps
	Network	RJ45 / WIFI 802.11b/g/n
	Working Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
	Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
	Power Input	DC12V-1A

	Power consumption	≤6W
	Dimension	205(L)×70(W)×55 (H)mm
	Weight	0.7kg